

Heavy Duty Jacking Castor Swivel Polyurethane Wheel 150mm 750kg Load JA6-150-SUB

This Extra Heavy Duty Jacking Castor with a 150mm heavy duty polyurethane wheel can lift loads an additional 76mm in vertical height. With a side mounted attachment plate jacking castors can be used on a variety of equipment and machinery that require vertical movement as well as horizontal. The jacking operation is achieved by a hexagonal spanner at the top of the jacking unit.
Flexello JA6SUB



Technical Specifications

	Bearing Type	Roller
	Bolt Hole Size (mm)	12
	Colour	No
	Jacking Unit Extension Height Max 76m	580
	Jacking Unit Height From Plate Lower Bolt Hole	240
	Load Capacity (kg)	750
	Max Load Capacity for 2 Jacking Castors	750
	Min Jacking Unit Extension Height	465
	Operating Method	Spanner
	Plate Dimension Length (mm)	152
	Plate Dimension Width (mm)	106
	Plate Hole Centres Length (mm)	114
	Plate Hole Centres Width (mm)	64
	Plate Hole Diameter	13
	Product Type	Jacking Castors
	Swivel Radius	135
	Thread Material	No
	Total Castor Height	186.5+ 76
	Total Height to Plate Lower Bolt Hole	225
	Tread Width (mm)	50
	Wheel Centre	Cast Iron
	Wheel Colour	Yellow
	Wheel Diameter(mm)	150
	Wheel Material	Polyurethane

Dimensions

